

# The CMH range



Wattage [W]	Volts [V]	Cap	Product Description	Product Code	Lumen [lm]	Colour	Operating position	Rated life (Vertical) [h]	Rated life (Horizontal) [h]	Length [mm]	Diameter [mm]	Energy Consumption [kWh]	EEC	Pack Qty
20	95	GU6.5	CMH20/TC/UVC/830/GU6.5	40399	1615	830	U	12,000	12,000	52	13	21.93	A	12
35	80-105	GU6.5	CMH35/T/UVC/930/U/GU6.5 PRECISE***	67685	4000	930	U*	18,000*	18,000*	52	12	TBD	TBD	12
35	93	GU6.5	CMH35/T/UVC/U/930/GU6.5 ULTRA	76122	3500	930	U	16,500	16,500	52	13	43.05	A+	12
35	95	GU6.5	CMH35/T/UVC/930/GU6.5	88656	3400	930	U	10,000	10,000	52	13	42.20	A+	12
35	95	GU6.5	CMH35/T/UVC/942/GU6.5	88657	3400	942	U	12,000	12,000	52	13	42.36	A	12

## ConstantColor™ – CMH Single Ended Mini



20	90	G8.5	CMH20/TC/UVC/U/830/G8.5 PLUS	39858	1650	830	U	12,000	12,000	85	14.5	21.78	A	12
35	90	G8.5	CMH35/T/UVC/U/830/G8.5 Plus	43273	3400	830	U	16,500	16,500	85	14.5	43.40	A+	12
35	90	G8.5	CMH35/TC/UVC/U942/G8.5	26348	3200	942	U	18,000	18,000	85	14.5	44.24	A	12
35	80-105	G8.5	CMH35/TC/UVC/U/930/G8.5 PRECISE***	67683	4000	930	U*	18000*	18000*	85	14.5	TBD	TBD	12
35	92	G8.5	CMH35/TC/UVC/U/930/G8.5 ULTRA	76120	3600	930	U	16,500	16,500	85	14.5	43.08	A+	12
70	90	G8.5	CMH70/TC/UVC/U/942/G8.5	26349	6200	942	U	15,000	15,000	85	14.5	80.43	A	12
70	85	G8.5	CMH70/TC/UVC/U/830/G8.5 PLUS	67698	7000	830	U	15,000	15,000	85	14.5	79.20	A+	12
70	90	G8.5	CMH70/TC/UVC/U/930/G8.5 PRECISE***	67681	7800	930	U*	18000*	18000*	85	14.5	TBD	TBD	12
70	90	G8.5	CMH70/TC/UVC/U/930/G8.5 ULTRA WHITE	63595	6700	930	U	18,000	18,000	85	14.5	80.61	A+	12
70	90	G8.5	CMH70/TC/UVC/U/930/G8.5 ULTRA	96751	6200	930	U	18,000	18,000	85	14.5	79.94	A+	12

## ConstantColor™ – CMH Single Ended



20	90	G12	CMH20/T/UVC/U/830/G12 PLUS	42708	1650	830	U	12,000	12,000	90	14.5	21.78	A	12
35	90	G12	CMH35/T/UVC/U/830/G12 PLUS	43272	3400	830	U	16,500	16,500	90	14.5	43.37	A+	12
35	80-105	G12	CMH35/T/UVC/U/930/G12 PRECISE***	67684	4000	930	U*	18000*	18000*	100	19	TBD	TBD	12
35	92	G12	CMH35/T/UVC/U/930/G12 ULTRA	76121	3600	930	U	16,500	16,500	90	19	43.06	A+	12
35	90	G12	CMH35/T/UVC/U/942/G12	92141	3200	942	U	18,000	18,000	90	14.5	44.57	A	12
70	90	G12	CMH70/T/UVC/U/830/G12	20005	6400	830	U	15,000	15,000	90	19	76.48	A+	12
70	90	G12	CMH70/T/UVC/U/942/G12	20013	6000	942	U	15,000	15,000	90	19	80.09	A+	12
70	90	G12	CMH70/T/UVC/U/930/G12 PRECISE***	67682	7800	930	U*	18000*	18000*	100	19	TBD	TBD	12
70	95	G12	CMH70/T/UVC/U/930/G12 ULTRA WHITE	63596	6600	930	U	18,000	18,000	90	19	81.31	A+	12
70	95	G12	CMH70/T/UVC/U/930/G12 ULTRA	96752	6400	930	U	18,000	18,000	90	19	80.08	A+	12
150	90	G12	CMH150/T/UVC/U/830/G12	20012	14000	830	U	12,000	12,000	100	19	160.27	A+	12
150	90	G12	CMH150/T/UVC/U/942/G12	20014	13000	942	U	12,000	12,000	100	19	164.22	A	12

## ConstantColor™ – CMH Double Ended



35	90	RX7s	CMH35/TD/UVC/830/RX7s	43278	3400	830	HOR±45°	-	15,000	118	21	41.99	A	12
70	90	RX7s	CMH70/TD/UVC/830/RX7s	36910	7000	N/A	HOR±45°	-	15,000	118	21	80.73	A+	12
70	90	RX7s	CMH70/TD/UVC/942/RX7s	38698	6200	N/A	HOR±45°	-	15,000	118	21	79.42	A+	12
150	96	RX7s-24	CMH150/TD/UVC/830/RX7s-24	36912	14500	N/A	HOR±45°	-	15,000	135	27	158.73	A+	12
150	96	RX7s-24	CMH150/TD/UVC/942/RX7s-24	38692	12500	N/A	HOR±45°	-	15,000	135	27	155.26	A+	12

\* Target performance

\*\* Expected availability in Q3 2013

Wattage [W]	Volts [V]	Cap	Product Description	Product Code	Candela [cd]	Beam Angle [°]	Colour	Operating position	Rated life (Vertical) [h]	Rated life (Horizontal) [h]	Length [mm]	Diameter [mm]	Energy Consumption [kWh]	EEC	Pack Qty
-------------	-----------	-----	---------------------	--------------	--------------	----------------	--------	--------------------	---------------------------	-----------------------------	-------------	---------------	--------------------------	-----	----------

## ConstantColor™ – CMH MR16 Precise



20	95	GX10	CMH20/MR16/UVC/830/GX10/SP	40400	9000	12	830	U	12,000	12,000	54.5	51	21.73	A	12
20	95	GX10	CMH20/MR16/UVC/830/GX10/FL GX10	40401	2900	25	830	U	12,000	12,000	54.5	51	21.70	A	12
20	95	GX10	CMH20/MR16/UVC/830/GX10/WFL GX10	42691	1500	40	830	U	12,000	12,000	54.5	51	21.76	A	12
35	80-105	GX10	CMH35/MR16/U/930/GX10/SP PRECISE***	67686	2500	12	930	U*	18,000*	18,000*	54.5	50	TBD	TBD	12
35	80-105	GX10	CMH35/MR16/U/930/GX10/FL PRECISE***	67687	2500	25	930	U*	18,000*	18,000*	54.5	50	TBD	TBD	12
35	80-105	GX10	CMH35/MR16/U/930/GX10/WFL PRECISE***	67697	2500	40	930	U*	18,000*	18,000*	54.5	50	TBD	TBD	12
35	93	GX10	CMH35/MR16/UVC/930/GX10/SP Ultra	76123	16000	12	930	U	16,500	16,500	54.5	51	43.00	A	12
35	93	GX10	CMH35/MR16/UVC/930/GX10/FL Ultra	76124	5500	25	930	U	16,500	16,500	54.5	51	43.00	A	12
35	93	GX10	CMH35/MR16/UVC/930/GX10/WFL Ultra	76125	3000	40	930	U	16,500	16,500	54.5	51	43.00	A	12
35	90	GX10	CMH35/MR16/UVC/930/GX10/SP GX10	88658	16000	12	930	U	10,000	10,000	54.5	51	42.21	A	12
35	90	GX10	CMH35/MR16/UVC/930/GX10/FL GX10	88659	5500	25	930	U	10,000	10,000	54.5	51	42.17	A	12
35	90	GX10	CMH35/MR16/UVC/930/GX10/WFL GX10	88660	3000	40	930	U	10,000	10,000	54.5	51	42.21	A	12
35	90	GX10	CMH35/MR16/UVC/942/GX10/SP GX10	88661	16000	12	942	U	12,000	12,000	54.5	51	42.26	A	12
35	90	GX10	CMH35/MR16/UVC/942/GX10/FL GX10	88662	5500	25	942	U	12,000	12,000	54.5	51	42.24	A	12
35	90	GX10	CMH35/MR16/UVC/942/GX10/WFL GX10	88663	3000	40	942	U	12,000	12,000	54.5	51	42.20	A	12