

# PARATHOM® PAR20/30/38, R50



Item name	Product number (EAN)	W <sup>1</sup>	Replace-ment for	lm <sup>1</sup>	cd	K	R <sub>a</sub>	∅ <sup>2</sup>	l [mm]	d [mm]	t [h] <sup>3</sup>	Ⓢ	No.
-----------	----------------------	----------------	------------------	-----------------	----	---	----------------	----------------	--------	--------	--------------------	---	-----

## OSRAM PARATHOM® ADVANCED PAR20 dimmable<sup>2</sup> – E27, 220–240 V, 30°, folding carton box

ADVANCED PAR20	4052899931299	6	50W	350	1,200	2,700	80	✓	87	64	40,000	A+	01
----------------	---------------	---	-----	-----	-------	-------	----	---	----	----	--------	----	----

## OSRAM PARATHOM® ADVANCED PAR30 dimmable<sup>2</sup> – E27, 220–240 V, 30°, folding carton box

ADVANCED PAR30	4052899938519	9	90W	766	1,800	2,700	80	✓	92	96	40,000	A+	02
----------------	---------------	---	-----	-----	-------	-------	----	---	----	----	--------	----	----

## OSRAM PARATHOM® ADVANCED PAR38 dimmable<sup>2</sup> – E27, 220–240 V, 30°, folding carton box

ADVANCED PAR38	4052899938526	14	120W	1,035	2,500	2,700	80	✓	129	121	40,000	A+	03
----------------	---------------	----	------	-------	-------	-------	----	---	-----	-----	--------	----	----

## OSRAM PARATHOM® ADVANCED R50 dimmable<sup>2</sup> – E27, 220–240 V, 30°, folding carton box

ADVANCED R50 40 30°	4052899938663	3.5	40W	230	600	2,700	80	✓	86	50	25,000	A+	04
---------------------	---------------	-----	-----	-----	-----	-------	----	---	----	----	--------	----	----

## OSRAM PARATHOM® ADVANCED R50 dimmable<sup>2</sup> – E14, 220–240 V, 30°, folding carton box

ADVANCED R50 40 30°	4052899938670	3.5	40W	230	600	2,700	80	✓	86	50	25,000	A+	05
---------------------	---------------	-----	-----	-----	-----	-------	----	---	----	----	--------	----	----

## OSRAM PARATHOM® R50 – E14, 220–240 V, 30°, folding carton box

R50 40 30°	4052899938656	3	40W	230	600	2,700	80	—	86	50	25,000	A++	05
------------	---------------	---	-----	-----	-----	-------	----	---	----	----	--------	-----	----

<sup>1</sup> All technical parameters apply to the complete lamp. Due to the complex manufacturing process of light emitting diodes, the specified typical values of the LED parameters merely represent purely statistical variables. They do not necessarily correspond to the actual technical parameters of each individual product, which can deviate from the typical value

<sup>2</sup> LED lamps can be operated with a wide variety of commercially-available dimmers; details and results of compatibility tests can be seen at [www.osram.com/dim](http://www.osram.com/dim) and in the additional technical product information sheets linked there

<sup>3</sup> L70/B50